

Table 2 — Residual marine fuels

Characteristic	Unit	Limit	Category ISO-F-												Test method reference
			RMA	RMB	RMD	RME	RMG				RMK				
			10 ^a	30	80	180	180	180,0	380,0	500,0	700,0	380	500	700	
Kinematic viscosity at 50 °C ^b	mm ² /s	max.	10,00	30,00	80,00	180,0	180,0	380,0	500,0	700,0	380,0	500,0	700,0	ISO 3104	
Density at 15 °C	kg/m ³	max.	920,0	960,0	975,0	991,0	991,0	991,0	991,0	991,0	1010,0	1010,0	1010,0	see 7.1 ISO 3675 or ISO 12185	
CCAI	—	max.	850	860	860	860	860	870	870	870	870	870	870	see 6.3 a)	
Sulfur ^c	mass %	max.	Statutory requirements												see 7.2 ISO 8754 ISO 14596
Flash point	°C	min.	60,0	60,0	60,0	60,0	60,0	60,0	60,0	60,0	60,0	60,0	60,0	see 7.3 ISO 2719	
Hydrogen sulfide ^d	mg/kg	max.	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	2,00	IP 570	
Acid number ^e	mg KOH/g	max.	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	ASTM D664	
Total sediment aged	mass %	max.	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	0,10	see 7.5 ISO 10307-2	
Carbon residue: micro method	mass %	max.	2,50	10,00	14,00	15,00	15,00	18,00	18,00	18,00	20,00	20,00	20,00	ISO 10370	
Pour point (upper) ^f	winter quality	max.	0	0	30	30	30	30	30	30	30	30	30	ISO 3016	
	summer quality	max.	6	6	30	30	30	30	30	30	30	30	30	ISO 3016	
Water	volume %	max.	0,30	0,50	0,50	0,50	0,50	0,50	0,50	0,50	0,50	0,50	0,50	ISO 3733	
Ash	mass %	max.	0,040	0,070	0,070	0,070	0,070	0,100	0,100	0,150	0,150	0,150	0,150	ISO 6245	
Vanadium	mg/kg	max.	50	150	150	150	150	350	350	350	450	450	450	see 7.7 IP 501, IP 470 or ISO 14597	
Sodium	mg/kg	max.	50	100	100	100	100	100	100	100	100	100	100	see 7.8 IP 501 IP 470	

Table 2 (continued)

Characteristic	Unit	Limit	Category ISO-F-										Test method reference			
			RMA	RMB	RMD	RME	RMG			RMK						
			10 ^a	30	80	180	180	380	500	700	380	500		700		
Aluminium plus silicon	mg/kg	max	25	40	40	50		60								see 7.9 IP 501, IP 470 or ISO 10478
Used lubricating oils (ULO): calcium and zinc; or calcium and phosphorus	mg/kg	—	The fuel shall be free from ULO. A fuel shall be considered to contain ULO when either one of the following conditions is met: calcium > 30 and zinc > 15; or calcium > 30 and phosphorus > 15										see 7.10 IP 501 or IP 470 IP 500			

^a This category is based on a previously defined distillate DMC category that was described in ISO 8217:2005, Table 1. ISO 8217:2005 has been withdrawn.

^b 1 mm²/s = 1cSt.

^c The purchaser shall define the maximum sulfur content in accordance with relevant statutory limitations. See 0.3 and Annex C.

^d Due to reasons stated in Annex D, the implementation date for compliance with the limit shall be 1 July 2012. Until such time, the specified value is given for guidance.

^e See Annex H.

^f Purchasers shall ensure that this pour point is suitable for the equipment on board, especially if the ship operates in cold climates.